



受力示意

配线图



参数	Specifications	技术指标/Technique
额定量程	Capacity	50, 100, 200, 500kg 1, 2, 3t
输出灵敏度	Reted output	1.5 ± 20% mV/V
零点输出	Zero Balance	± 5% mV/V
蠕变	Creep (30min)	≤ 0.1% F.S.
非线性	Non-linearity	≤ 0.5% F.S.
滞后	Hysteresis	≤ 0.2% F.S.
重复性	Repeatability	≤ 0.2% F.S.
输入电阻	Input impedance	700 ± 10 Ω
输出电阻	Output impedance	700 ± 10 Ω
温度灵敏度漂移	Temp. effect on output	0.05% F.S. / 10 °C
零点温度漂移	Temp. effect on zero	0.05% F.S. / 10 °C
绝缘电阻	Insulation resistance	≥ 5000M Ω / 100V (DC)
激励电压	Recommended excitation	5 ~ 12V
最大激励电压	Maximum excitation	15V
温度补偿范围	Compensated Temp Range	-10 ~ 60 °C
工作温度范围	Operating Temp Range	-20 ~ 80 °C
安全过载	Safe overload	150% F.S.
极限过载	Ultimate overload	200% F.S.
电缆线尺寸	Cable size	Φ 3X3m
材料	Material	Stainless steel/不锈钢

未标偏差极限偏差数值					第一角画法		 <b>费波斯</b> 费波斯测量技术(常州)有限公司 <small>FIBOS Measurement Technology (CHANGZHOU) CO., LTD</small>
尺寸分段	f (精密级)	m (中等级)	c (粗糙级)	v (最粗级)	比例	1:1	
0-6	±0.05	±0.1	±0.2	±0.5	设计 审核 批准	品名: FA110参数 图号: 21120802   版本号: A 材料:	
6-30	±0.1	±0.2	±0.5	±1			
30-120	±0.15	±0.3	±0.8	±1.5			
120-400	±0.2	±0.5	±1.2	±2.5			
400-1000	±0.3	±0.8	±2	±4			
1000-2000	±0.5	±1.2	±3	±6			
2000-6000	±1	±2	±4	±8			